# ACCUD

## ACCURATE MEASUREMENT




See full product range at: accud.nz

# Coating Thickness Gauge

Series CFN1500B




## Features

Integrated F and N type probe
F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic subtracts (iron, steel)
N type probe is used to measure the thickness of non-conductive coatings (varnish ,enamel, plastic and so on) on conductive subtracts (zinc, copper, aluminum)
Large display screen
V-type probe to make the cylinder measurement easier
With um/mil unit conversion
Automatic power on/ off
With back light

## Specifications

| Part No | Specification |
|---|---|
| AC-CFN1500B | Range: 0 ~ 1500□m<br>Accuracy: 2□m(0 ~ 100□m)<br>Accuracy: 3%(100 ~ 1500□m)<br>Resolution: 0.1□m (0 ~ 99.9□m)<br>Resolution: 1□m (100 ~ 1500□m)<br>Min. measuring area: 25×25mm<br>Min. curvature: convexity: 5mm; concave: 30mm<br>Min substrate thickness: magnetic material: 0.2mm; non magnetic material: 0.05mm<br>Memory: 30 sets<br>Power supply: AAAbatteries<br>Dimension(L×W×H): 120×52×26mm<br>Weight: 170g<br><br>Included accessories<br>Main unit: 1pc<br>Calibration foil: 1set<br>Calibration base: 1set<br>AAA battery: 2pcs |

© 2026 M Gamer Pty Ltd