ACCUD

ACCURATE MEASUREMENT



See full product range at: accud.nz

Coating Thickness Gauge

Series CN/CF/CFN1500



Features

F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic subtracts (iron, steel)
N type probe is used to measure the thickness of non-conductive coatings (varnish ,enamel, plastic and so on) on conductive subtracts (zinc, copper, aluminum)
External interchangeable probe
Single and continuous working mode
Low and high limits setting with judgement
With average calculation
With comparison measurement function
With temperature compensation
Turn off automatically

Specifications

Part No	Specification
AC-CF1500	Probe type: F Range: 0 ~ 1500□m Accuracy: 2□m (0 ~ 100□m) Accuracy: 2%(100 ~ 1500□m) Resolution: 0.1□m (0 ~ 999□m) Resolution: 1□m (1000 ~ 1250□m) Memory: 500 Power: 3×AAAbatteries Dimension(L×W×H): 150×50×29mm Weight: 170g Included accessories Main unit: 1pc Calibration foil: 1 set Calibration base: 1 set USB cable: 1pc AAA battery: 3pcs

© 2026 M Gamer Pty Ltd

Part No	Specification
AC-CFN1500	Probe type: F and N Range: 0 ~ 1500㎛ Accuracy: 2㎛ (0 ~ 100㎛) Accuracy: 2%(100 ~ 1500㎛) Resolution: 0.1㎛ (0 ~ 999㎛) Resolution: 1㎛ (1000 ~ 1250㎛) Memory: 500 Power: 3×AAAbatteries Dimension(L×W×H): 150×50×29mm Weight: 170g Included accessories Main unit: 1pc Calibration foil: 1 set Calibration base: 1 set USB cable: 1pc AAA battery: 3pcs
AC-CN1500	Probe type: N Range: 0 ~ 1500㎛ Accuracy: 2㎛ (0 ~ 100㎛) Accuracy: 2%(100 ~ 1500㎛) Resolution: 0.1㎛ (0 ~ 999㎛) Resolution: 1㎛ (1000 ~ 1250㎛) Memory: 500 Power: 3×AAAbatteries Dimension(L×W×H): 150×50×29mm Weight: 170g Included accessories Main unit: 1pc Calibration foil: 1 set Calibration base: 1 set USB cable: 1pc AAA battery: 3pcs

© 2026 M Gamer Pty Ltd